

BENDER+WIRTH HOLDERS OVERVIEW

MechaTronix offers a wide range of LED coolers, specifically developed and thermally validated for all major brands of LED modules.

Our ECO partnerships also include close cooperations with key manufacturers of LED accessories like lenses, reflectors and LED holders.

Mechanical compatibility of all components is what our MechaTronix LED coolers stand for.

This document provides an easy overview of all MechaTronix LED coolers which are compatible with the Bender+Wirth LED holders.

With the combination of these LED coolers and the B+W LED holders, the assembly of LED COB's becomes an easy plug-and-play job without soldering and with a guaranteed perfect thermal fitting on the heat sink.

Permissible COB dimensions (mm)	LED COB Holders
12.5 x 12.5	630 series - 660x
12 x 15	630 series - 652x
13.5 x 13.5	630 series - 634x
4pcs 13.5 x 13.5	MTX CoolConnect® holder 2x2MX-02
15.85 x 15.85	630 series - 641x
4pcs 15.85 x 15.85	MTX CoolConnect® holder 2x2MX-01
16 x 19	630 series - 638x

Permissible COB dimensions (mm)	LED COB Holders
17.85 x 17.85	630 series - 637 x
19 x 19	630 series - 633x
19 x 24	630 series - 663x
20 x 24	630 series - 632x
24 x 24	630 series - 639x
28 x 28	630 series - 631x MTX CoolConnect® holder COB 28x28
38 x 38	MTX CoolConnect® holder COB 38x38 MTX CoolConnect® holder COB 38x38 dual

- · This is a non-binding overview of available B+W LED holders compatibility on MTX LED heat sinks.
- The B+W LED Holder Series 630 offers a wide range of different standard COB holders with different housings. For all possible variants, compatible LED CoB and further technical details, please visit http://www.bender-wirth.com

630 series housings:



LowProfile



Bayonet50



3Hook



Hekla




Lena

MTX CoolConnect® holders (Co-development with B+W):



2x2MX-01 / 02



COB 28x28 / 38x38 / 38x38 dual

LPF - PIN FIN LED COOLERS





Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder

ø47mm - H68mm - Rth 3.9°C/W

Cooling performance 1,300 - 2,500 lm Black or clear anodised





Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder

ø60mm - H50mm - Rth 4.0°C/W

Cooling performance 1,200 - 2,300 lm Black anodised



LED Pin Fin cooler

LED Pin Fin cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder

ø67mm - H68mm - Rth 2.1°C/W

Cooling performance 2,300 - 4,600 lm Black or clear anodised



LPF8050-ZHC

LED Pin Fin cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder

ø80mm - H50mm - Rth 2.34°C/W

Cooling performance 2,000 - 4,000 lm Black anodised

LPF8668-ZHC

LED Pin Fin cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder

ø86mm - H68mm - Rth 1.46°C/W

Cooling performance 3,300 - 6,500 lm Black or clear anodised



LPF11180-ZHE

LED Pin Fin cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder

ø111mm - H80mm - Rth 1.07°C/W

Cooling performance 4,800 - 9,600 lm Black or clear anodised

COOLSTAR® - DESIGNER LED STAR COOLERS



CoolStar® Black / White 4740

Designer LED Star cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630

ø47mm - H40mm - Rth 5°C/W

Cooling performance 1,000 - 2,000 lm Black anodized or white electro-coating finishing



CoolStar® Black / White 4760

Designer LED Star cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630

ø47mm - H60mm - Rth 4.17°C/W


Cooling performance 1,200 - 2,400 lm Black anodized or white electro-coating finishing



CoolStar® Black / White 6730

Designer LED Star cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630




Cooling performance 1,600 - 3,100 lm Black anodized or white electro-coating finishing



CoolStar® Black / White 6760

Designer LED Star cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630



Cooling performance 2,100 - 4,200 lm Black anodized or white electro-coating finishing



CoolStar® Black / White 8630

Designer LED Star cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630

ø86mm - H30mm - Rth 2.08°C/W

Cooling performance 2,300 - 4,600 lm Black anodized or white electro-coating finishing



CoolStar® Black / White 8660

Designer LED Star cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630

ø86mm - H60mm - Rth 1.56°C/W

Cooling performance 3,100 - 6,100 lm Black anodized or white electro-coating finishing





MODULED - MODULAR LED COOLERS



ModuLED Pico 4750

Modular Passive LED Star cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder

ø47mm - H50mm - Rth 5.3°C/W

Cooling performance 900 - 1,800 lm Black or clear anodised



ModuLED Pico 4780

Modular Passive LED Star cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder.

ø47mm - H80mm - Rth 4.2°C/W

Cooling performance 1,200 - 2,300 lm Black or clear anodised



ModuLED Nano 7050

Modular Passive LED Star cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder

ø70mm - H50mm - Rth 2.2°C/W

Cooling performance 2,200 - 4,300 lm Black or clear anodised



ModuLED Nano 7080

Modular Passive LED Star cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder

ø70mm - H80mm - Rth 1.8°C/W

Cooling performance 2,700 - 5,300 lm Black or clear anodised



ModuLED Micro 8630

Modular Passive LED Star cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder

ø86mm - H30mm - Rth 1.8°C/W

Cooling performance 2,700 - 5,300 lm Black or clear anodised



ModuLED Micro 8650

Modular Passive LED Star cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder

ø86mm - H50mm - Rth 1.5°C/W

Cooling performance 3,200 - 6,400 lm Black or clear anodised



ModuLED Micro 8680

Modular Passive LED Star cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder

ø86mm - H80mm - Rth 1.2°C/W

Cooling performance 4,000 - 8,000 lm Black or clear anodised



ModuLED 9950

Modular Passive LED Star cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder

ø99mm - H50mm - Rth 1.34°C/W

Cooling performance 3,600 - 7,200 lm Black or clear anodised

MODULED - MODULAR LED COOLERS

ModuLED 9980

Modular Passive LED Star cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder

ø99mm - H80mm - Rth 1.02°C/W

Cooling performance 4,700 - 9,400 lm Black or clear anodised



ModuLED Xtra 9950

Modular Passive LED Star cooler

Mounting holes for assembly of LED COB with B+W 630 holder and MTX CoolConnect® holder COB 28x28 (Codevelopment with B+W)

ø99mm - H50mm - Rth 1.34°C/W

Cooling performance 3,600 - 7,200 lm Black or clear anodised



ModuLED Xtra 9980

Modular Passive LED Star cooler

Mounting holes for assembly of LED COB with B+W 630 holder and MTX CoolConnect® holder COB 28x28 (Codevelopment with B+W)

ø99mm - H80mm - Rth 1.02°C/W

Cooling performance 4,700 - 9,400 lm Black or clear anodised



ModuLED Mega 13420

Modular Passive LED Star cooler

Mounting holes for assembly of LED COB with B+W 630 holder and MTX CoolConnect® holder COB 28x28 / 38x38 / 38x38 dual (Co-development with B+W)

ø134mm - H20mm - Rth 1.32°C/W

Cooling performance 3,700 - 7,300 lm Black anodised



ModuLED Mega 13450

Modular Passive LED Star cooler

Mounting holes for assembly of LED COB with B+W 630 holder and MTX CoolConnect® holder COB 28x28 / 38x38 / 38x38 dual (Co-development with B+W)

ø134mm - H50mm - Rth 0.88°C/W

Cooling performance 5,500 - 11,000 lm Black anodised



ModuLED Mega 134100

Modular Passive LED Star cooler

Mounting holes for assembly of LED COB with B+W 630 holder and MTX CoolConnect® holder COB 28x28 / 38x38 / 38x38 dual (Co-development with B+W)

ø134mm - H100mm - Rth 0.67°C/W

Cooling performance 7,200 - 14,300 lm Black anodised



ModuLED Giga 15220

Modular Passive LED Star cooler

Mounting holes for assembly of LED COB with B+W 630 holder and MTX CoolConnect® holder COB 28x28 / 38x38 / 38x38 dual (Co-development with B+W)

ø152mm - H20mm - Rth 1.13°C/W

Cooling performance 4,300 - 8,500 lm Black anodised



ModuLED Giga 15250

Modular Passive LED Star cooler

Mounting holes for assembly of LED COB with B+W 630 holder and MTX CoolConnect® holder COB 28x28 / 38x38 / 38x38 dual (Co-development with B+W)

ø152mm - H50mm - Rth 0.7°C/W

Cooling performance 6,800 - 13,500 lm Black anodised

ICELED ACTIVE LED COOLING



IceLED 450

Modular Active LED Star cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder

ø99mm - H45mm - Rth 0.58°C/W

Fan Voltage 12Vdc - 50mA Fan Speed 1500RPM Cooling performance 8,200 - 16,400 lm



IceLED 550

Modular Active LED Star cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder.

ø99mm - H55mm - Rth 0.46°C/W

Fan Voltage 12Vdc - 50mA Fan Speed 1500RPM Cooling performance 10,500 - 21,000 lm



IceLED Xtra 550

Modular Active LED Star cooler

Mounting holes for assembly of LED COB with B+W 630 holder and MTX CoolConnect® holder COB 28x28 (Codevelopment with B+W)

ø99mm - H55mm - Rth 0.46°C/W

Fan Voltage 12Vdc - 50mA Fan Speed 1500RPM Cooling performance 10,500 - 21,000 lm



IceLED Ultra

Modular Active LED Star cooler

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder

ø99mm - H75mm - Rth 0.25°C/W

Fan Voltage 12Vdc - 230mA Fan Speed 3000RPM Cooling performance 19,000 - 38,000 lm



IceLED Xtra Ultra

Modular Active LED Star cooler

Mounting holes for assembly of LED COB with B+W 630 holder and MTX CoolConnect® holder COB 28x28 (Codevelopment with B+W)

ø99mm - H75mm - Rth 0.25°C/W

Fan Voltage 12Vdc - 230mA Fan Speed 3000RPM Cooling performance 19,000 - 38,000 lm



IceLED Ultra VS

Modular Active LED Star cooler

Mounting holes for assembly of LED COB with B+W 630 holder and MTX CoolConnect® holder COB 28x28 (Codevelopment with B+W)

ø99mm - H75mm - Rth 0.26°C/W

Fan Voltage 12Vdc - 160mA Fan Speed 2600RPM Cooling performance 14,500 - 29,000 lm

HBG & COOLBAY® - HIGH BAY LED COOLING



ModuLED Mega 13450-HBG

High Bay LED cooler with direct mounting holes for assembly of LED COB with B+W 630 holder or MTX CoolConnect® holder COB 28x28 / 38x38 / 38x38 dual (Codevelopment with B+W) and Mean Well HRG series driver

ø134mm - H50mm - Rth 0.88°C/W

Cooling performance 5,500 - 11,000 lm Black anodised



ModuLED Mega 134100-HBG

High Bay LED cooler with direct mounting holes for assembly of LED COB with B+W 630 holder or MTX CoolConnect® holder COB 28x28 / 38x38 / 38x38 dual (Codevelopment with B+W) and Mean Well HRG series driver

ø134mm - H100mm - Rth 0.67°C/W Cooling performance 7,200 - 14,300 lm

Black anodised



ModuLED Giga 152100-HBG

High Bay LED cooler with direct mounting holes for assembly of LED COB with B+W 630 holder or MTX CoolConnect® holder COB 28x28 / 38x38 / 38x38 dual (Codevelopment with B+W) and Mean Well **HBG** series driver

ø152mm - H100mm - Rth 0.52°C/W Cooling performance 9,000 - 18,000 lm Black anodised



ModuLED Giga 152150-HBG

High Bay LED cooler with direct mounting holes for assembly of LED COB with B+W 630 holder or MTX CoolConnect® holder COB 28x28 / 38x38 / 38x38 dual (Codevelopment with B+W) and Mean Well **HBG** series driver

ø152mm - H150mm - Rth 0.46°C/W Cooling performance 10,500 - 21,000 lm Black anodised



CoolBay® Giga-A

Advanced High Bay LED cooler with CoolTube® quadruple closed-loop heat pipe structure

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder, and for Mean Well HBG-160 LED driver & various accessories

ø152mm - H200mm - Rth 0.34°C/W Cooling performance 14,500 - 29,000 lm Black nano coating



CoolBay® Giga-B

Advanced High Bay LED cooler with CoolTube® quadruple closed-loop heat pipe structure

Mounting holes for assembly of LED COB with B+W 630 holder and MTX CoolConnect® holder COB 28x28 / 38x38 / 38x38 dual (Co-development with B+W), and for Mean Well HBG-160 LED driver & various accessories ø152mm - H200mm - Rth 0.34°C/W Cooling performance 14,500 - 29,000 lm

Black nano coating



CoolBav® Tera-B

Advanced High Bay LED cooler with CoolTube® quadruple closed-loop heat pipe structure

Mounting holes for assembly of LED COB with B+W 630 holder and MTX CoolConnect® holder COB 28x28 / 38x38 / 38x38 dual (Co-development with B+W), and for Mean Well HBG-240 LED driver & various accessories ø192mm - H250mm - Rth 0.22°C/W Cooling performance 22,000 - 44,000 lm Black nano coating



CoolBav® Tera-A

Advanced High Bay LED cooler with CoolTube® quadruple closed-loop heat pipe structure

Zhaga Book 3 mounting holes for assembly of LED COB with B+W 630 holder, and for Mean Well HBG-240 LED driver & various accessories

ø192mm - H250mm - Rth 0.22°C/W Cooling performance 22,000 - 44,000 lm Black nano coating



COOLBLOCK® & COOLBEAM® 2X2MX FAMILY

CoolBlock® SQ-01 2x2MX



Square Pin Fin LED Cooler for 2x2MX platform. Direct mounting holes for MTX & B+W co-development CoolConnect® holder 2x2MX-01 / -02 enabling assembly for 4pcs 15.85x15.85mm or 13.5x13.5mm COBs, and Ledil Strada 2x2MX lenses for IP67 waterproof with just a few screws

W96mm - L96mm - H61.5mm - Rth 1.45°C/W

Cooling performance 3,300 - 6,500 lm Black electro-coating

The CoolBeam® kits allow assembly from 3 all the way up to 12 units of the CoolBlock® 2x2MX platform, to create your next high bay, industrial flood light or horticulture top light project from 4,000 to 60,000 lumen.



CoolBeam® SQ3-01



CoolBeam® SQ4-01



CoolBeam® SQ Dual



CoolBeam® SQ Triple



