










Type	Profile				Description	Manual App Control	
	Fixture ID	Model / Name	Icon	Fixture mode		Dimmer: N ↓ ↻	
Misc.	526**	CBU-TED		TE-PC/1ch/Dim{OHI}	One channel 50/60Hz trailing edge phase cut dimmer	Dimmer: N ↓ ↻	
	11766	CBU-TED (linear)		TE-PC/1ch/Dim{OHI}	One channel 50/60Hz trailing edge phase cut dimmer. Linear dimming curve.	Dimmer: N ↓ ↻	
	8123	CBU-TED (log)		TE-PC/1ch/Dim{OHI}	One channel 50/60Hz trailing edge phase cut dimmer. Logarithmic dimming curve.	Dimmer: N ↓ ↻	
	3534	TED/Presence		Sensor	Fixture providing presence. Presence can be activated from smart switch, push button or dedicated presence sensor.	-	It appears under "Sensors" tab.

** Default profile

Additional Information

Summary of some terms and abbreviations that have been used throughout the document.

Abbreviation:	Description:
N ↓ ↻	Trailing edge dimmer output.
Linear	Linear dimming curve.
Log	Logarithmic dimming curve.



Revision history

Date:	Version:	Description:
26/09/2023	1.0	Initial release.

