## carus

### **Data Sheet Carus Connect**

#### E27 560 Lumen Smart White

#### **Technical Data**

Supply Voltage 220-240V | 50/60Hz
Rated Power 8,0W
Lumen per Watt 70lm/W
Energy Efficiency Class A+
AC Operation Yes
DC Operation No


Rated Luminous Flux 10 lm - 560 lmColor Temperature 2.200 K - 4.500 KColor Rendering Index >95Color Consistency  $SDCM \le 6$ Beam Angle  $150^{\circ}$ 

Number of Switching Cycles 25.000
Rated Lifetime 25.000h
Luminous Flux Maintenance Factor at End of Life Time 0,7
Starting Time <0,5s

Operating Temperature -20°C bis +40°C Storage Temperature -20°C bis +60°C

IP Protection Class IP50





#### **Dimming and Color Temperature Selection**

Carus Connect Smart White is dimmable via Casambi smartphone app. It can be controlled by Casambi xPress and by existing switches with appropriate Casambi app settings.

Dimming with phase dimmers is not possible.

Color temperature settings can also be done with Casambi App, Casambi xPress or existing switches which are configurated with the Casambi app.

#### **Dimensions**

Height	108mm
Diameter	60mm
Weight	76g
Form	A60
Base	E27

# Ø 60 80

#### **Application Information**

For indoor use in dry environment Applicable in luminaires designed for outdoor use


#### **Disposal Information**

LED-Lamps need an environmentally compatible disposal Carus LED-Lamps meet RoHS and REACH requirements




## carus


#### **Spectral Distribution 2.200K**



#### **Spectral Distribution 2.700K**



#### **Spectral Distribution 4.500K**



**Packaging**Folding Box

**Article Number** 1016455

**EAN Code** 4260406080406

**Dimensions of Single Packaging Unit** 

80mm x 72mm x 146mm

#### **Manufacturer Data**

Carus GmbH & Co. KG Rosenstraße 8 D-35037 Marburg

T: +49 (0)6421 - 604 500 E: info@carus-world.com W: www.carus-world.com

WEEE-Reg.-Nr.: DE 13926631