

MechaTronix in LED

LPF11180-ZHE Edison Opto Pin Fin LED Cooler ø111mm



Features & Benefits

- The LPF11180-ZHE Zhaga Pin Fin LED cooler is specifically designed for luminaires using the Citizen CITELED LED COB. Mechanical compatibility with direct mounting of the LED modules to the LED cooler and thermal performance matching the lumen packages.
- For spot and downlight designs from 2,000 to 6,000 lumen
- Thermal resistance Rth 1.07°C/W
- Modular design with mounting holes foreseen for Edison Opto EdiPower II / EdiPower III HM16, HM24, HM30, HM40 LED COB and Edilex Spot Light Module (SLM) LED modules, direct mounting or by use of Zhaga Book 3 LED holder.
- Diameter 111mm - Standard height 80mm
Other heights on request
- Forged from highly conductive aluminum



Order Information

 Zhaga

 EDISON

Example : LPF11180-ZHE-B

LPF11180-ZHE- **1**

- 1** Anodising Color
B - Black
C - Clear
Z - Custom (specify)

The LPF11180-ZHE pin fin LED cooler is designed in this way that you can mount various LED modules on the same LED cooler

Simple mounting with 2 screws

Recommended screw force 6lb/in


Screws are available from MechaTronix

MechaTronix in LED

LPF11180-ZHE Edison Opto Pin Fin LED Cooler ø111mm



Product Details



Model n°

LPF11180-ZHE

Dimension (mm)* ¹	ø111 x h80
Volume (mm ³)	210075
Cooling Surface (mm ²)	115637
Weight (gr)	567
Thermal Resistance (°C/W)* ²	1.07
Power Pd (W)* ³	50
Heat Sink Material	AL1070

*¹ 3D files are available in ParaSolid, STP and IGS on request

*² The thermal resistance Rth is determined with a calibrated heat source of 30mm x 30mm central placed on the heat sink, Tamb 40° and an open environment. Reference data @ heat sink to ambient temperature rise Ths-amb 50°C
The thermal resistance of a LED cooler is not a fix value and will vary with the applied dissipated power Pd

*³ Dissipated power Pd. Reference data @ heat sink to ambient temperature rise Ths-amb 50°C
The maximal dissipated power needs to be verified in function of required case temperature Tc or junction temperature Tj and related to the estimated ambient temperature where the light fixture will be placed
Please be aware the dissipated power Pd is not the same as the electrical power Pe of a LED module

To calculate the dissipated power please use the following formula: $P_d = P_e \times (1 - \eta_L)$

Pd - Dissipated power

Pe - Electrical power

η_L = Light efficiency of the LED module

Notes:

- MechaTronix reserves the right to change products or specifications without prior notice.
- Mentioned models are an extraction of full product range.
- For specific mechanical adaptations please contact MechaTronix.

MechaTronix in LED

LPF11180-ZHE Edison Opto Pin Fin LED Cooler ø111mm



Mounting Options

The LPF11180-ZHE Pin Fin LED cooler is standard foreseen from a variety of mounting holes which allow direct mounting of LED engines, COB's and secondary optics on the LED heat sink.

In this way mechanical afterwork and related costs can be avoided, and lighting designers can standardize their designs on a limited number of LED coolers.

Below you find an overview of Edison Opto LED modules and COB's which standard fit on the LPF11180-ZHE Pin Fin LED cooler.

MechaTronix performs thermal validation tests on each of the LED modules mounted on the LED cooler and publishes this data in the LED brand thermal validation reports.

For a full overview of available LED coolers for Edison Opto LEDs, please refer to the Edison Opto LED cooler overview on www.led-heatsink.com/Download.php or scan the QR code here.




Edison Opto LED Modules and COB's



Edison Opto with headquarters in Chung-Ho Dist, New Taipei City, Taiwan is a professional LED manufacture with specializes in designing and producing High-power LEDs, solid state lighting applications, LED sensors and SPDIFs. In response to rapid growth of capacity demand, Edison Opto has established factories in Dongguan and Yangzhou China and subsidiaries in USA and Germany. Edison Opto COB LED modules outstand in light quality and are available in the broadest lumen and CRI range available on the market.

Mounting indicator marks overview

MechaTronix recommends the use of a high thermal conductive interface between the LED module and the LED cooler. Either thermal grease, a thermal pad or a phase change thermal pad thickness 0.1-0.15mm is recommended. Thermal pads or phase change thermal pads can be pre-applied from MechaTronix.



Edison Opto EdiPower II & EdiPower III HM series

Model Names 16W - 30W

- 2PHM16xxxx
- 2PHM24xxxx
- 2PHM30xxxx

Mounting



- With Zhaga Book 3 LED holder
- BJB Spotlight connector 47.319.2021
- Ideal Industries Chip-Lok™ holder 50-2103CT
- TE Connectivity Lumawise type Z50 2213254-1
- TE Connectivity Lumawise type Z50 2213254-2
- Mounting with 2 screws M3 x 6mm
- Green indicator marks

Model Names 40W

- 2PHM40xxxx

Mounting

- With Zhaga Book 3 LED holder
- BJB Spotlight connector 47.319.2033
- Ideal Industries Chip-Lok™ holder 50-2204CT
- Mounting with 2 screws M3 x 6mm
- Green indicator marks



MechaTronix in LED

LPF11180-ZHE Edison Opto Pin Fin LED Cooler ø111mm



Mounting Options



Edison Opto EdiLex Spot Light Module (SLM)

Model names

- 5PHR09xxxx
- 5PHR11xxxx
- 5PHR22xxxx
- 5PHV35xxxx

Mounting

- Direct mounting with 2 screws M3 x 6mm
Green indicator marks

Reflector ring Mounting



- This optional ring can be mounted on top of the Edison Opto EdiLex spot light module and provides in this way an easy plug-and-play attachment of various reflectors.
- Mounting with 3 screws M3 x 10mm
Yellow indicator marks

MechaTronix in LED


LPF11180-ZHE Edison Opto Pin Fin LED Cooler ø111mm



Drawings & Dimensions



Example: LPF11180-ZHE



Thermal Data

$P_d = P_e \times (1 - \eta_L)$			LED Light efficiency, η_L (%)			Heat sink to ambient thermal resistance R_{hs-amb} (°C/W)	Heat sink to ambient temperature rise T_{hs-amb} (°C)
			17%	20%	25%	LPF11180-ZHE	LPF11180-ZHE
Dissipated Power P_d (W)	20	Electrical Power P_e (W)	24	25	26.66	1.25	27.0
	30		36.14	37.5	40	1.18	35.2
	40		48.19	50	53.33	1.12	43.3
	50		60.24	62.5	66.66	1.06	51.4
	60		72.28	75	80	1.00	59.6
	70		84.33	87.5	93.33	0.94	67.7

Heat sink to ambient temperature rise T_{hs-amb} (°C)

— LPF11180-ZHE

