

Features

- Compact size with stand and mounting flexibility
- Excellent microprocessor control guarantees high reliability
- Auto restart while AC is recovering
- Simulated sine wave
- Cold start function



MODEL	NANO 400	NANO 600	NANO 800
CAPACITY	400VA / 240W	600VA / 360W	800VA / 480W
INPUT			
Voltage		220 / 230 / 240Vac	
Voltage Range		180-270Vac	
Frequency Range		50Hz (auto sensing)	
OUTPUT			
AC Voltage Regulation (Batt. Mode)		±10%	
Frequency Range (Batt. Mode)		50Hz ±1 Hz	
Transfer Time		Typical 2-6 ms	
Waveform (Batt. Mode)		Simulated Sine Wave	
BATTERY			
Battery Type & Number	12V / 4.5Ah x 1	12V / 7Ah x 1	12V / 9Ah x 1
Typical Recharge Time		8 hours up to 90% capacity	
INDICATORS			
AC Mode		Green lighting	
Battery Mode		Green flashing	
ALARM			
Battery Mode		Sounding every 10 seconds	
Low Battery		Sounding every second	
Fault		Continuously sounding	
PROTECTION			
Full Protection		Overload, discharge and overcharge protection	
PHYSICAL			
Dimension, D X W X H (mm)		228 x 82.5 x 207 (Vertically stand)	
Net Weight (kgs)	2.2	2.7	3.1
ENVIRONMENT			
Humidity		0-90% RH @ 0- 40°C (non-condensing)	
Noise Level		Less than 40dB	

* Product specifications are subject to change without further notice