

CE

Declaration of Conformity

For the following equipment :

Product Name: Switching Power Supply

Model Designation: UHP-200x-y(x=R or Blank; y=3.3, 4.2, 5, 12, 15, 24, 36, 48)

is herewith confirmed to comply with the requirements set out in the Council Directive, the following standards were applied :

RoHS Directive (2011/65/EU)

Low Voltage Directive (2014/35/EU):

EN60950-1:2006+A11+A1+A12+A2

TUV certificate No : R50383440

Electromagnetic Compatibility Directive (2014/30/EU) :

EMI (Electro-Magnetic Interference)

Conducted emission / Radiated emission

| Conducted emission / Ra | EN55032:2015 | | Class B |
|---------------------------|--|--------------|--------------------------------------|
| Harmonic current | EN61000-3-2:2014 | | |
| Voltage flicker | EN61000-3-3:2013 | | |
| EMS (Electro-Magnetic | Susceptibility) | | |
| EN55024:2010+A1:2015 | EN61000-6-2:2005 | | |
| ESD air | EN61000-4-2:2009 | Level 3 | 8KV |
| ESD contact | EN61000-4-2:2009 | Level 2 | 4KV |
| RF field susceptibility | EN61000-4-3:2006+A1:2008+A2:2010 | Level 3 | 10V/m |
| EFT bursts | EN61000-4-4:2012 | Level 3 | 2KV/5KHz |
| Surge susceptibility | EN61000-4-5:2014 | Level 3 | 2KV/Line-Line |
| Surge susceptibility | EN61000-4-5:2014 | Level 4 | 4KV/Line-Earth |
| Conducted susceptibility | EN61000-4-6:2014 | Level 3 | 10V |
| Magnetic field immunity | EN61000-4-8:2010 | Level 4 | 30A/m |
| Voltage dip, interruption | EN61000-4-11:2004 >95% dip 0.5 periods 3 | 0% dip 25 pe | riods >95% interruptions 250 periods |

Note:

A component power supply with load will be installed into final equipment which consists of an electronically shielded metal enclosure. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again.

The EMC tests mentioned above are performed using a well defined metal plate to simulate said metal enclosure. For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies" (as available on <u>http://www.meanwell.com</u>)" and TDF (Technical Documentation File).

This Declaration is effective from serial number HB7xxxxxx

Person responsible for marking this declaration :

| MEAN WELL Enterprises Co., Ltd. (Manufacturer Name) | | | |
|---|---------------------------|---|-------------|
| No.28, Wuquan 3rd Rd., Wugu Dist., (Manufacturer Address) | New Taipei City 248, 1 | Taiwan | \bigcirc |
| Johnny Huang/Manager, Certification Center (Name / Position) | : (Signature) | Alex Tsai/Director, Marketing Department : (Name / Position) | (Signature) |
| Taiwan (Place) | Nov. 15th, 2017 (Date) | | |



CE

Declaration of Conformity

For the following equipment :

Product Name: Switching Power Supply

Model Designation: UHP-200x-y(x=R or Blank; y=3.3, 4.2, 5, 12, 15, 24, 36, 48)

is herewith confirmed to comply with the requirements set out in the Council Directive, the following standards were applied :

RoHS Directive (2011/65/EU)

Low Voltage Directive (2014/35/EU) :

EN60335-1:2012+A11/EN62233:2008

TUV certificate No : R50386757

Electromagnetic Compatibility Directive (2014/30/EU) :

EMI (Electro-Magnetic Interference)

Conducted emission / Radiated emission

EN55014-1:2006+A1:2009+A2:2011

| Harmonic current | EN61000-3-2:2014 |
|------------------|------------------|
| | |

Voltage flicker EN61000-3-3:2013

EMS (Electro-Magnetic Susceptibility)

| EN55014-2:2015 EN61000-6-2:2005 | | | | |
|---------------------------------|--|---------------|--------------------------------------|--|
| ESD air | EN61000-4-2:2009 | Level 3 | 8KV | |
| ESD contact | EN61000-4-2:2009 | Level 2 | 4KV | |
| RF field susceptibility | EN61000-4-3:2006+A1:2008+A2:2010 | Level 3 | 10V/m | |
| EFT bursts | EN61000-4-4:2012 | Level 3 | 2KV/5KHz | |
| Surge susceptibility | EN61000-4-5:2014 | Level 3 | 2KV/Line-Line | |
| Surge susceptibility | EN61000-4-5:2014 | Level 4 | 4KV/Line-Earth | |
| Conducted susceptibility | EN61000-4-6:2014 | Level 3 | 10V | |
| Magnetic field immunity | EN61000-4-8:2010 | Level 4 | 30A/m | |
| Voltage dip, interruption | EN61000-4-11:2004 >95% dip 0.5 periods | 30% dip 25 pe | riods >95% interruptions 250 periods | |

Note:

A component power supply with load will be installed into final equipment which consists of an electronically shielded metal enclosure. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again.

The EMC tests mentioned above are performed using a well defined metal plate to simulate said metal enclosure. For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies".(as available on <u>http://www.meanwell.com</u>)" and TDF (Technical Documentation File).

This Declaration is effective from serial number HB7xxxxxx

Person responsible for marking this declaration :

| MEAN WELL Enterprises Co., Ltd. | | | |
|--|------------------------|--|-------------|
| (Manufacturer Name) | | | |
| No.28, Wuquan 3rd Rd., Wugu Dist., I | New Taipei City 248, 1 | Taiwan | |
| (Manufacturer Address) | 1 | | M |
| Johnny Huang/Manager, Certification Center | : Tolum | Alex Tsai/Director, Marketing Department : | (-10) |
| (Name / Position) | (Signature) | (Name / Position) | (Signature) |
| Taiwan | Nov. 15th, 2017 | | |
| (Place) | (Date) | | |